

## DEFENDER FR™



### DESCRIPTION

- DEFENDER FR™ Limited Flame Resistant Coveralls
- 68 gsm Self-Extinguishing Fabric
- Serged Seams
- Zipper Front with Elastic Back & Wrists
- Attached Hood & Boots
- Tensile Strength (D5034): MD: 24.0 lbf., CD: 24.9 lbf.
- NFPA 701 Flame Propagation of Textiles & Films
- ASTM D6413 Flame Resistance of Textiles
- Not Designed for Arc Flash

Ideal for: Refineries, Mining, Utilities, Welding, Plant Visitors, Laboratories, Steel mills, Foundries, Clinics, Hospitals, and other work environments where hazardous & non-hazardous liquid and dry particulate contaminants may be present.



### DESCRIPTION:

DEFENDER FR™, Coverall, FR, Hood, Boots : FRC400

Limited Flame Resistant Coverall, Composition 57.4% Viscose/43% PET, Elastic Wrists, Waist, Hood & Boots, Covered Zip Front, Fabric Basis Weight: 73.3 grams/square meter, Meets Flame Resistance Requirements of NFPA 701

### CERTIFICATIONS & RATINGS:

Made with FDA Approach Materials for food contact Applications. (U.S. Code of Federal Regulations, 21CFR, Parts 170-199)

Prolongs the life of primary FR garments by providing a secondary level of protection against sparks, dirt & grime.

### APPLICATIONS:



HOSPITALS



WELDING



MINING



LABORATORIES

### ORDERING:

**Unit of Sale:** One Case  
**Packaging:** 25 EA/Polybag  
**Case Pack:** 25 EA/Case  
**COO:** China  
**Available Sizes:** L-5XL

Case Weight (lbs)	L	XL	2XL	3XL	4XL	5XL
	67	67	67	67	67	67

### BARCODES:

ITEM	DOZEN	CASE
FRC400L	796326351161	50796326351166
FRC400XL	796326351178	50796326351173
FRC4002XL	796326351185	50796326351180
FRC4003XL	796326351192	50796326351197
FRC4004XL	796326351208	50796326351203
FRC4005XL	796326351215	50796326351210

### CARE:

Dispose after each use.

### Corporate Headquarters:

4025 Viscount Avenue  
 Memphis, TN 38118  
 Phone 800.458.8763  
 Fax 901.458.3343

**CORE SAFETY PROTECTION**  
[www.cordovasafety.com](http://www.cordovasafety.com)

### West Coast Office:

433 Cheryl Lane (Dock Door 14)  
 City of Industry, CA 91789  
 Phone 909.590.2679  
 Fax 909.590.3130